

## BOGE C-2 series

Compact. Efficient. Quiet.



### TECHNICAL DATA

BOGE Model	Max. pressure*	Effective free air delivery	Motor power	Dimensions	Compressed Air Outlet	Sound Pressure Level	Weight
	psig	cfm	hp	W" x D" x H"		dB(A)	
C 12-2 N	100	73	15	63.4 x 36 x 54.3	NPT 1"	63	1151
C 12-2 N	125	65	15	63.4 x 36 x 54.3	NPT 1"	63	1151
C 12-2 N	150	60	15	63.4 x 36 x 54.3	NPT 1"	63	1151
C 12-2 N	190	46	15	63.4 x 36 x 54.3	NPT 1"	63	1151
C 12-2 L N	100	69	15	63.4 x 36 x 54.3	NPT 1"	63	1140
C 12-2 L N	150	67	15	63.4 x 36 x 54.3	NPT 1"	63	1140
C 12-2 LFN	100	19 – 73	15	63.4 x 36 x 54.3	NPT 1"	63	1228
C 12-2 LFN	110	19 – 71	15	63.4 x 36 x 54.3	NPT 1"	63	1228
C 12-2 LFN	125	19 – 67	15	63.4 x 36 x 54.3	NPT 1"	63	1228
C 12-2 LFN	150	19 – 59	15	63.4 x 36 x 54.3	NPT 1"	63	1228
C 12-2 LFN	190	19 – 46	15	63.4 x 36 x 54.3	NPT 1"	63	1228
C 15-2 N	100	96	20	63.4 x 36 x 54.3	NPT 1"	65	1173
C 15-2 N	125	89	20	63.4 x 36 x 54.3	NPT 1"	65	1173
C 15-2 N	150	79	20	63.4 x 36 x 54.3	NPT 1"	65	1173
C 15-2 N	190	64	20	63.4 x 36 x 54.3	NPT 1"	65	1173
C 15-2 L N	100	79	20	63.4 x 36 x 54.3	NPT 1"	65	1140
C 15-2 L N	150	77	20	63.4 x 36 x 54.3	NPT 1"	65	1140
C 15-2 LFN	100	19 – 95	20	63.4 x 36 x 54.3	NPT 1"	65	1206
C 15-2 LFN	110	19 – 92	20	63.4 x 36 x 54.3	NPT 1"	65	1206
C 15-2 LFN	125	19 – 87	20	63.4 x 36 x 54.3	NPT 1"	65	1206
C 15-2 LFN	150	18 – 78	20	63.4 x 36 x 54.3	NPT 1"	65	1206
C 15-2 LFN	190	18 – 67	20	63.4 x 36 x 54.3	NPT 1"	65	1206

\* Also available in pressures up to 200 PSI - C/F

## BOGE C-2 series

Compact. Efficient. Quiet.

### TECHNICAL DATA

BOGE Model	Max. pressure*	Effective free air delivery	Motor power	Dimensions	Compressed Air Outlet	Sound Pressure Level	Weight lbs
	psig	cfm	hp	W" x D" x H"		dB(A)	
C 18-2 N	100	117	25	63.4 x 36 x 54.3	NPT 1"	68	1250
C 18-2 N	125	108	25	63.4 x 36 x 54.3	NPT 1"	68	1250
C 18-2 N	150	96	25	63.4 x 36 x 54.3	NPT 1"	68	1250
C 18-2 N	190	82	25	63.4 x 36 x 54.3	NPT 1"	68	1250
C 18-2 LF N	100	19 – 115	25	63.4 x 36 x 54.3	NPT 1"	68	1250
C 18-2 LF N	110	19 – 112	25	63.4 x 36 x 54.3	NPT 1"	68	1250
C 18-2 LF N	125	19 – 106	25	63.4 x 36 x 54.3	NPT 1"	68	1250
C 18-2 LF N	150	18 – 93	25	63.4 x 36 x 54.3	NPT 1"	68	1250
C 18-2 LF N	190	25 – 82	25	63.4 x 36 x 54.3	NPT 1"	68	1250
C 22-2 N	100	135	30	63.4 x 36 x 54.3	NPT 1"	69	1316
C 22-2 N	125	125	30	63.4 x 36 x 54.3	NPT 1"	69	1316
C 22-2 N	150	113	30	63.4 x 36 x 54.3	NPT 1"	69	1316
C 22-2 N	190	97	30	63.4 x 36 x 54.3	NPT 1"	69	1316
C 22-2 LF N	100	19 – 135	30	63.4 x 36 x 54.3	NPT 1"	69	1327
C 22-2 LF N	110	19 – 131	30	63.4 x 36 x 54.3	NPT 1"	69	1327
C 22-2 LF N	125	19 – 124	30	63.4 x 36 x 54.3	NPT 1"	69	1327
C 22-2 LF N	150	18 – 108	30	63.4 x 36 x 54.3	NPT 1"	69	1327
C 22-2 LF N	190	25 – 97	30	63.4 x 36 x 54.3	NPT 1"	69	1327

BOGE Model	With dryer (D)		With 120 gal receiver (R)		With 120 gal receiver and dryer (DR)	
	Dimensions W" x D" x H"	Weight lbs	Dimensions W" x D" x H"	Weight lbs	Dimensions W" x D" x H"	Weight lbs
C 12-2 & C 15-2 N	63.4 x 36 x 54.3	1239 & 1284	80.2 x 36 x 73.4	1484 & 1506	80.2 x 36 x 73.4	1572 & 1616
C 12-2 L & C 15-2 L N	63.4 x 36 x 54.3	1228 & 1250	80.2 x 36 x 73.4	1473	80.2 x 36 x 73.4	1561 & 1583
C 12-2 LF & C 15-2 LF N	63.4 x 36 x 54.3	1316	80.2 x 36 x 73.4	1561 & 1539	80.2 x 36 x 73.4	1649
C 18-2 & C 22-2 N	63.4 x 36 x 54.3	1360 & 1426	80.2 x 36 x 73.4	1583 & 1649	80.2 x 36 x 73.4	1693 & 1759
C 18-2 LF & C 22-2 LF N	63.4 x 36 x 54.3	1360 & 1438	80.2 x 36 x 73.4	1583 & 1660	80.2 x 36 x 73.4	1693 & 1770

\* Also available in pressures up to 200 PSI - C/F