

BOGE S-3 series

Designed to last longer



TECHNICAL DATA

BOGE type	Max. pressure*	Effective free air delivery	Rated output		Dimensions	Compressed air outlet	Weight silenced	Weight super silenced
			Main drive	Fan motor				
	psig	cfm	hp	hp	W x D x H (inches)	ANSI	lbs	lbs
S 40-3 N	100	192	40	1.0	64 x 39 x 57	NPT 1 1/4	1857	—
S 40-3 N	115	184	40	1.0	64 x 39 x 57	NPT 1 1/4	1857	—
S 40-3 N	125	184	40	1.0	64 x 39 x 57	NPT 1 1/4	1857	—
S 40-3 N	150	167	40	1.0	64 x 39 x 57	NPT 1 1/4	1857	—
S 40-3 N	190	140	40	1.0	64 x 39 x 57	NPT 1 1/4	1857	—
SLF 40-3 N	100	48 - 196	40	1.0	73 x 39 x 57	NPT 1 1/4	1863	—
SLF 40-3 N	115	46 - 188	40	1.0	73 x 39 x 57	NPT 1 1/4	1863	—
SLF 40-3 N	125	46 - 188	40	1.0	73 x 39 x 57	NPT 1 1/4	1863	—
SLF 40-3 N	150	46 - 168	40	1.0	73 x 39 x 57	NPT 1 1/4	1863	—
SLF 40-3 N	190	44 - 148	40	1.0	73 x 39 x 57	NPT 1 1/4	1863	—
S 50-3 N	100	240	50	2.0	64 x 39 x 57	NPT 1 1/4	1859	1925
S 50-3 N	115	225	50	2.0	64 x 39 x 57	NPT 1 1/4	1859	1925
S 50-3 N	125	225	50	2.0	64 x 39 x 57	NPT 1 1/4	1859	1925
S 50-3 N	150	205	50	2.0	64 x 39 x 57	NPT 1 1/4	1859	1925
S 50-3 N	190	175	50	2.0	64 x 39 x 57	NPT 1 1/4	1859	1925
SLF 51-3 N	100	87 - 264	50	1.5	81 x 42 x 58	NPT 1 1/2	2756	2866
SLF 51-3 N	115	83 - 253	50	1.5	81 x 42 x 58	NPT 1 1/2	2756	2866
SLF 51-3 N	125	83 - 253	50	1.5	81 x 42 x 58	NPT 1 1/2	2756	2866
SLF 51-3 N	150	79 - 223	50	1.5	81 x 42 x 58	NPT 1 1/2	2756	2866
SLF 51-3 N	190	75 - 182	50	1.5	81 x 42 x 58	NPT 1 1/2	2756	2866

BOGE S-3 series

Designed to last longer

BOGE type	Max. pressure*	Effective free air delivery	Rated output		Dimensions W x D x H (inches)	Compressed air outlet ANSI	Weight silenced lbs	Weight super silenced lbs
	psig		cfm	Main drive hp				
S 60-3 N	100	269	60	2.0	64 x 39 x 57	NPT 1 1/4	2192	2258
S 60-3 N	115	258	60	2.0	64 x 39 x 57	NPT 1 1/4	2192	2258
S 60-3 N	125	258	60	2.0	64 x 39 x 57	NPT 1 1/4	2192	2258
S 60-3 N	150	231	60	2.0	64 x 39 x 57	NPT 1 1/4	2192	2258
S 60-3 N	190	196	60	2.0	64 x 39 x 57	NPT 1 1/4	2192	2258
S 61-3 N	100	287	60	2.0	79 x 42 x 58	NPT 1 1/2	2602	2712
S 61-3 N	115	273	60	2.0	79 x 42 x 58	NPT 1 1/2	2602	2712
S 61-3 N	125	273	60	2.0	79 x 42 x 58	NPT 1 1/2	2602	2712
S 61-3 N	150	240	60	2.0	79 x 42 x 58	NPT 1 1/2	2602	2712
S 61-3 N	190	208	60	2.0	79 x 42 x 58	NPT 1 1/2	2602	2712
SLF 61-3 N	100	114 - 292	60	2.0	81 x 42 x 58	NPT 1 1/2	3043	3153
SLF 61-3 N	115	110 - 279	60	2.0	81 x 42 x 58	NPT 1 1/2	3043	3153
SLF 61-3 N	125	110 - 279	60	2.0	81 x 42 x 58	NPT 1 1/2	3043	3153
SLF 61-3 N	150	102 - 242	60	2.0	81 x 42 x 58	NPT 1 1/2	3043	3153
SLF 61-3 N	190	76 - 203	60	2.0	81 x 42 x 58	NPT 1 1/2	3043	3153
S 75-3 N	100	359	75	3.0	79 x 42 x 58	NPT 1 1/2	2778	2888
S 75-3 N	115	344	75	3.0	79 x 42 x 58	NPT 1 1/2	2778	2888
S 75-3 N	125	344	75	3.0	79 x 42 x 58	NPT 1 1/2	2778	2888
S 75-3 N	150	298	75	3.0	79 x 42 x 58	NPT 1 1/2	2778	2888
S 75-3 N	190	256	75	3.0	79 x 42 x 58	NPT 1 1/2	2778	2888
SLF 75-3 N	100	81 - 354	75	3.0	81 x 42 x 58	NPT 1 1/2	3303	3413
SLF 75-3 N	115	78 - 339	75	3.0	81 x 42 x 58	NPT 1 1/2	3303	3413
SLF 75-3 N	125	78 - 339	75	3.0	81 x 42 x 58	NPT 1 1/2	3303	3413
SLF 75-3 N	150	74 - 294	75	3.0	81 x 42 x 58	NPT 1 1/2	3303	3413
SLF 75-3 N	190	77 - 255	75	3.0	81 x 42 x 58	NPT 1 1/2	3303	3413
S 100-3 N	100	475	100	3.0	79 x 42 x 58	NPT 1 1/2	2994	3105
S 100-3 N	115	452	100	3.0	79 x 42 x 58	NPT 1 1/2	2994	3105
S 100-3 N	125	452	100	3.0	79 x 42 x 58	NPT 1 1/2	2994	3105
S 100-3 N	150	387	100	3.0	79 x 42 x 58	NPT 1 1/2	2994	3105
S 100-3 N	190	336	100	3.0	79 x 42 x 58	NPT 1 1/2	2994	3105
S 271-3 N	100	1260	270	10.0	123 x 76 x 85	4" ANSI	10141	10362
S 271-3 N	115	1147	270	10.0	123 x 76 x 85	4" ANSI	10141	10362
S 271-3 N	125	1147	270	10.0	123 x 76 x 85	4" ANSI	10141	10362
S 271-3 N	150	1101	270	10.0	123 x 76 x 85	4" ANSI	10141	10362
S 271-3 N	190	932	270	10.0	123 x 76 x 85	4" ANSI	10141	10362
SLF 271-3 N	100	300-1260	270	10.0	125 x 76 x 85	4" ANSI	11245	11465
SLF 271-3 N	115	300-1186	270	10.0	125 x 76 x 85	4" ANSI	11245	11465
SLF 271-3 N	125	300-1186	270	10.0	125 x 76 x 85	4" ANSI	11245	11465
SLF 271-3 N	150	290-1088	270	10.0	125 x 76 x 85	4" ANSI	11245	11465
SLF 271-3 N	190	292-932	270	10.0	125 x 76 x 85	4" ANSI	11245	11465
S 341-3 N	100	1471	340	15.0	123 x 76 x 85	4" ANSI	10585	10800
S 341-3 N	115	1427	340	15.0	123 x 76 x 85	4" ANSI	10585	10800
S 341-3 N	125	1427	340	15.0	123 x 76 x 85	4" ANSI	10585	10800
S 341-3 N	150	1329	340	15.0	123 x 76 x 85	4" ANSI	10585	10800
S 341-3 N	190	1140	340	15.0	123 x 76 x 85	4" ANSI	10585	10800