

BOGE SRHV series

Flexible Booster – unbeatable efficiency



TECHNICAL DATA

BOGE Model	Supply PSI		Output PSI		CFM / 580 PSI		Pump	Pump	Motor		Dimensions	Weight
	Min	Max	Min	Max	Min	Max	RPM	Cyls	kW	HP	W" x D" x H"	LBS
SRHV 200-5	29	73	232	580	11	31	830	2	5.5	7.5	52 x 30 x 35	529
SRHV 250-5	29	73	232	580	19	38	1010	2	7.5	10	52 x 30 x 35	551
SRHV 450-5	29	73	232	580	28	71	1200	3	11	15	52 x 30 x 35	573
SRHV 540-5	29	73	232	580	37	86	1450	3	15	20	52 x 30 x 35	595
SRHV 170-10	87	145	232	580	30	53	695	2	7.5	10	52 x 30 x 35	540
SRHV 280-10	87	145	232	580	53	91	1130	2	11	15	52 x 30 x 35	551
SRHV 420-10	87	145	232	580	80	135	1130	3	15	20	52 x 30 x 35	595
SRHV 470-10	87	145	232	580	92	157	1270	3	18.5	25	52 x 30 x 35	606

Free air delivery as per ISO 1217:2009 Appendix C measured at 80% maximum pressure