

## BOGE C series

Compact and robust



## TECHNICAL DATA

BOGE type	Max. pressure	Effective free air delivery	Motor power	Dimensions***	Compressed air outlet	Sound pressure level***	Weight***
	bar						
C 3 L*	10	0.234	2.2	817 x 520 x 495	G 1/2	61	105
C 4 L*	10	0.311	3	817 x 520 x 495	G 1/2	62	110
C 4 L*	13	0.204	3	817 x 520 x 495	G 1/2	62	110
C 5 L*	10	0.536	4	817 x 520 x 495	G 1/2	67	125
C 7 L*	10	0.707	5.5	817 x 520 x 495	G 1/2	68	130
C 7 L*	13	0.525	5.5	817 x 520 x 495	G 1/2	68	130
C 10 L	8	1.05	7.5	1500 x 784 x 800	G 3/4	59.5	395
C 10 L	10	1.03	7.5	1500 x 784 x 800	G 3/4	59.5	395
C 15 L	8	1.81	11	1500 x 784 x 800	G 3/4	68	425
C 15 L	10	1.74	11	1500 x 784 x 800	G 3/4	68	425
C 20 L	8	2.25	15	1500 x 784 x 800	G 3/4	69	435
C 20 L	10	2.22	15	1500 x 784 x 800	G 3/4	69	435
C 4	8	0.427	3	480 x 907 x 955	G 1/2	59	190
C 4	10	0.340	3	480 x 907 x 955	G 1/2	59	190
C 4	13	0.219	3	480 x 907 x 955	G 1/2	59	190
C 5	8	0.601	4	480 x 907 x 955	G 1/2	63	195
C 5	10	0.506	4	480 x 907 x 955	G 1/2	63	195
C 5	13	0.386	4	480 x 907 x 955	G 1/2	63	195
C 7	8	0.847	5.5	480 x 907 x 955	G 1/2	64	210
C 7	10	0.736	5.5	480 x 907 x 955	G 1/2	64	210
C 7	13	0.576	5.5	480 x 907 x 955	G 1/2	64	210
C 9	8	1.180	7.5	480 x 987 x 1234	G 1/2	68	215
C 9	10	1.060	7.5	480 x 987 x 1234	G 1/2	68	215
C 9	13	0.870	7.5	480 x 987 x 1234	G 1/2	68	215
C 15	8	1.740	11	722 x 1060 x 1740	G 1	67	398
C 15	10	1.530	11	722 x 1060 x 1740	G 1	67	398
C 15	13	1.330	11	722 x 1060 x 1740	G 1	67	398
C 9 LF	7.5	0.27 - 1.29	7.5	1020 x 677 x 723	G 1/2	72	208
C 9 LF	8	0.26 - 1.26	7.5	1020 x 677 x 723	G 1/2	72	208
C 9 LF	10	0.25 - 1.14	7.5	1020 x 677 x 723	G 1/2	72	208
C 9 LF	13	0.24 - 0.97	7.5	1020 x 677 x 723	G 1/2	72	208
C 15 F	8	0.39 - 1.74	11	722 x 1060 x 1735	G 1	67	424
C 15 F	10	0.36 - 1.53	11	722 x 1060 x 1735	G 1	67	424
C 15 F	13	0.27 - 1.33	11	722 x 1060 x 1735	G 1	67	424

\* not available in super silenced version

\*\* changed design

\*\*\* super silenced version

# BOGE C series

Compact and robust



## TECHNICAL DATA

BOGE type	with dryer (D)		with receiver (R)			with receiver and dryer (DR)		
	Dimensions***	Weight***	Volume	Dimensions***	Weight***	Volume	Dimensions***	Weight***
	W x D x H (mm)	kg	liter	W x D x H (mm)	kg	liter	W x D x H (mm)	kg
C 3 L*	-	-	90	1185 x 550 x 1010	155	160	1723 x 675 x 1205	225
C 4 L*	-	-	90	1185 x 550 x 1010	160	160	1723 x 675 x 1205	230
C 5 L*	-	-	90	1185 x 550 x 1010	175	160	1723 x 675 x 1205	245
C 7 L*	-	-	90	1185 x 550 x 1010	180	160	1723 x 675 x 1205	250
C 10 L	-	-	350	1820 x 835 x 1495	515	350	2040 x 835 x 1500	550
C 15 L	-	-	350	1820 x 835 x 1495	555	350	2040 x 835 x 1500	590
C 20 L	-	-	350	1820 x 835 x 1495	575	350	2040 x 835 x 1500	610
C 4	480 x 990 x 1235	210	270	1815 x 910 x 1594	325	270	1815 x 910 x 1594	365
C 5	480 x 990 x 1235	215	270	1815 x 910 x 1594	330	270	1815 x 910 x 1594	365
C 7	480 x 990 x 1235	230	270	1815 x 910 x 1594	345	270	1815 x 910 x 1594	375
C 9	480 x 990 x 1235	235	270	1815 x 910 x 1594	350	270	1815 x 910 x 1594	380
C 15**	1072 x 1060 x 1735	498	350	1815 x 840 x 2085	508	350	1950 x 870 x 1990	544
C 9 LF	-	-	270	1720 x 790 x 1440	323	270	1720 x 745 x 1400	370
C 15 F	1072 x 1060 x 1735	524	-	-	-	-	-	-

\* not available in super silenced version

\*\* changed design

\*\*\* super silenced version